# **SBRC** Battery Rack Charger

## Overview

The Shure Battery Rack Charger (SBRC) provides a seamless, touring-ready battery charging and storage solution. Interchangeable charging modules support a variety of Shure Lithium-ion batteries, accommodating up to eight batteries in a single rack space. An easy-to-read, front-panel LCD screen displays critical parameters including charge levels, time-to-full, and battery health indicators such as temperature and cycle count. When connected to a network, Shure Wireless Workbench® and ShurePlus Channels software provide remote monitoring of battery status.

#### **Features**

- Comprehensive status display with straightforward three-button interface control
- Easily visible charge status by percentage and time-to-full readings in hours and minutes Battery health tracking metrics indicate percentage of original capacity and cycle count Remote monitoring of battery status through Shure Wireless Workbench® software
- Interchangeable charging modules allow users to mix and match up to eight Shure bodypack and handheld transmitter batteries Charges batteries to 50 percent capacity within one hour and full capacity within three hours

- Storage mode prepares batteries for optimal long-term storage Charges Shure SB900, SB900A, AXT910, and AXT920 rechargeable batteries

## **Specifications**

Battery Type	Up to 8 rechargeable Li-lon batteries	
Charge Time	50%=1 hour; 100%=3 hours	
Charging Module Type	Up to 4 charging modules in any combination	
Operating Temperature Range	−18 °C (0 °F) to 63 °C (145 °F)	
Battery Charging Temperature Range	0 °C (32 °F) to 60 °C (140 °F)	
Storage Temperature Range	−29 °C (−20 °F) to 74 °C (165 °F)	
Dimensions	$44\mathrm{mm} \times 483\mathrm{mm} \times 366\mathrm{mm}$ (1.7 in. $\times$ 19.0 in. $\times$ 14.4 in.), H $\times$ W $\times$ D	
Weight	4.4 kg (9.8 lbs), without batteries or charging modules	
Housing	Steel; Extruded aluminum	
Power Requirements	100 to 240 V AC, 50-60 Hz	
Current Drain	1.8 A RMS (referenced at 90 V AC)	

#### Networking


Network Interface	Ethernet 10/100 Mbps
Network Addressing Capability	DHCP or Manual IP address

## **Furnished Accessories**


(Region Dependent)	IEC AC Power Cable (1)	90XN1371	Hardware Kit (1)
C803	Shielded 3-foot Ethernet Cable (1)	30B13476	Mounting Screws for Charger Modules (8)

# **Optional Accessories**

AXT901	Charging Module for AXT910
AXT902	Charging Module for AXT920
SBC-AX	Charging Module for SBC900A



SBRC Rack Charger Front



SBRC Rack Charger Back



Europe, Middle East, Africa: Shure Europe GmbH Jakob-Dieffenbacher-Str. 12, 75031 Eppingen, Germany

Phone: +49-7262-92490 Fax: +49-7262-9249114 Email: info@shure.de www.shure.eu